



ON-TRACK PLANT ENGINEERING CONFORMANCE CERTIFICATE

This certificate issued in accordance with RIS-1530-PLT Issue 6.

NAME OF CERTIFICATION BODY AEGIS Certification Services Ltd	ACCREDITATION CODE AC
------------------------------------------------------------------------------	----------------------------------------

Machine Class/Description	Road Rail Machine Case 988 SP2S (Type 9B)
Vehicle Owner	Shovlin Ltd
Issue Date	05 September 2018
Expiry Date	31 August 2025

Vehicle Number: **99709 940513-3**

First of Class	No
Certificate Number of First of Class	NS/0162/17
First of Type	No
Certificate Number of First of Type	AC/0022/18

Authorised by:



Luigi D'Angelo
AEGIS PAB Signatory

Official Stamp



Reason for Issue and Scope of Work

Previous Certificate:

RRV originally accepted in accordance with the requirements of RIS-1530-PLT Issue 1. Fitment of direct-acting rail wheel disc brakes certified in accordance with the requirements of RIS-1530-PLT Issue 2.

Plant Asset Manager Copy

Certificate Number: AC/0123/18

This certificate:
 Increase in on/off-tracking cant to 150mm.
 Installation of air brake system.
 Installation of GKD RCI System.
 Upgrade to RIS-1530-PLT issue 6.
 Increase number of towed trailers to 4.

Deviations Associated with this Certificate

Reference None
Title None

Previous Certificate Number: RT/EA/0138/12

Approved Maintenance Instructions

ID No.	Title	Issue No.	Date
SPMM0001	Case 988 Rail Mounted Excavator Operation and Maintenance Handbook	6	March 2018
AJH080	Hydrovane Compressor Maintenance	1	22/04/2014

Machine Data

Gross Mass	21,800 kg		
Tailswing gauge exceedance	580 mm	Tailswing Height	1430 mm
Hydraulic park brake pressure	0-60 bar	Hydraulic service brake pressure	60 bar
Air service brake pressure	8.5 bar	Air park brake pressure	8.5 bar
Gauge	W6a	Software version (inc. RCI)	9.28

Approved Values

Maximum number of people	2		
Main load lifting point SWL	10,000 kg	Auxiliary lifting point SWL	5,000 kg
Maximum towed load	46000 kg	Maximum number of trailers	4

Approved Track Conditions

	Travelling Mode	Working Mode	On/off-tracking
Maximum gradient	1:25	1:25	1:25
Maximum cant	200 mm	150 mm	150 mm
Minimum curve radius	80 m	80 m	

Approved Maximum Speeds

	Travelling Mode	Working Mode
Plain Line	10 mph	10 mph
Switches and Crossings	5 mph	5 mph
Raised check and guard rails	5 mph	5 mph
Reverse	5 mph	5 mph
Towing	10 mph	10 mph

Limitations of Use

1. The machine shall not be used outside a possession.
2. The maximum number of people transported on this machine shall not exceed the value given in the Approved Values section of this ECC.
3. Lifts shall not exceed any SWL given in the Approved Values section of this ECC.
4. The maximum towed load shall not exceed the value given in the Approved Values section of this ECC.
5. The maximum number of trailers shall not exceed the number given in the Approved Values section of this ECC.
6. The machine shall not be used on track conditions in excess of those given in the Approved Track Conditions section of this ECC.
7. The machine speed shall not exceed the values given in the Approved Maximum Speeds section of this ECC.
8. The machine shall only be on/off-tracked at a RRAP or temporary crossing.
9. When travelling, mirrors shall be folded in.
10. When working, the counterweight, boom, dipper and attachments can be out of gauge. See Machine Data section of this ECC.
11. The machine shall **NOT** on/off-track, travel or work on live conductor-rail lines.
12. For access/egress, the machine may only operate with the door to the cab adjacent to a cess or a line closed to all train movements or the Method Statement safe system of work must take account of adequate safe clearances to adjacent lines.
13. Movement of boom towards backward stability limit shall be at moderate/low speed.

Supplementary Information

1. This machine's / re-approval for seven years was assessed against RIS-1530-PLT issue 6.
2. Duty chart reference: Case 988 232259 YTZ 1.80m+3.13m+2.10m 3 Sept 2018.
3. Machine is a rail-conversion of road multi-purpose excavator with 1.8m boom, 3.13m artic and 2.1m dipper arm.
4. It may work with a range of attachments through the dipper arm link pins or approved auxiliary lifting point.



- 5. The machine is fitted with a low performance vertical and lateral Movement Limiting Device.

Chassis / Serial Number	CGG0232259
Fleet Number	YTZ
Rexquote Number	1591

Authorised by:

Luigi D'Angelo
AEGIS PAB Signatory