


Liebherr 924


Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP
Unlocked Rail Cant -150mm



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP
Unlocked Rail Cant -50mm



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**

Unlocked Rail Cant 50mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**

Unlocked Rail Cant 150mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**

Locked Rail Cant -150mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**


Locked Rail Cant -50mm



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP
Locked Rail Cant 50mm



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP

Locked Rail Cant 150mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift BP**

Unlocked Road




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	71.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift BP**

Locked Road



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	71.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**

Unlocked Rail Cant -150mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**


Unlocked Rail Cant -50mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP
Unlocked Rail Cant 50mm - Tandem Lift**




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**

Unlocked Rail Cant 150mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**


Locked Rail Cant -150mm - Tandem Lift



Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**


Locked Rail Cant -50mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP
Locked Rail Cant 50mm - Tandem Lift**




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift BP**


Locked Rail Cant 150mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift BP
Unlocked Road - Tandem Lift




Units in Tonnes

1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	47.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift BP
Locked Road - Tandem Lift**



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	47.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Unlocked Rail Cant -150mm



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Unlocked Rail Cant -50mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Unlocked Rail Cant 50mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Unlocked Rail Cant 150mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Locked Rail Cant -150mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Locked Rail Cant -50mm



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Locked Rail Cant 50mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Locked Rail Cant 150mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift ALP1**

Unlocked Road



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	71.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift ALP1

Locked Road



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	71.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Unlocked Rail Cant -150mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**


Unlocked Rail Cant -50mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1
Unlocked Rail Cant 50mm - Tandem Lift**




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**

Unlocked Rail Cant 150mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1**


Locked Rail Cant -150mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			


Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1
Locked Rail Cant -50mm - Tandem Lift**



Liebherr 924


Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1
Locked Rail Cant 50mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift ALP1
Locked Rail Cant 150mm - Tandem Lift**



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift ALP1**

Unlocked Road - Tandem Lift



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	47.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift ALP1**

Locked Road - Tandem Lift



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	47.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Unlocked Rail Cant -150mm




Units in Tonnes

1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH
Unlocked Rail Cant -50mm



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Unlocked Rail Cant 50mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Unlocked Rail Cant 150mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	67.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**


Locked Rail Cant -150mm



Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Locked Rail Cant -50mm




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Locked Rail Cant 50mm



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Locked Rail Cant 150mm



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	90.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift QH**

Unlocked Road



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	71.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift QH

Locked Road



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	71.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Unlocked Rail Cant -150mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Unlocked Rail Cant -50mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Unlocked Rail Cant 50mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**

Unlocked Rail Cant 150mm - Tandem Lift




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	45.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH**


Locked Rail Cant -150mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH
Locked Rail Cant -50mm - Tandem Lift**




MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

Max Capacity Contours of Radius(m) Plots 1.9m Dipper

Gradient 1 in -25 Height 2m Lift QH


Locked Rail Cant 50mm - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924


**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Gradient 1 in -25 Height 2m Lift QH
Locked Rail Cant 150mm - Tandem Lift**



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	60.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift QH
Unlocked Road - Tandem Lift**



Units in Tonnes


1 2 3 4 5 6 7

MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	47.0%
COMMENT:			

Liebherr 924

**Max Capacity Contours of Radius(m) Plots 1.9m Dipper
Level Ground Height 2m Lift QH**

Locked Road - Tandem Lift



MACHINE & MODEL:	Liebherr 924	REFERENCE:	BP, ALP & QH
SERIAL No:	K119110	DATE OF CHART:	2-Jan-2020
EQUIPMENT:	2.08m + 3.40m + 1.82m	SAFETY FACTOR:	47.0%
COMMENT:			